MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				





MODEL No.	SH4140-RL-TAF
MATERIAL	HEAD & BODY - DIE CAST AL
	BOLT,NUT, ROLLER & ETC. - SUS304
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 1/2
COLIOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

■ Operating Characteristics

OF max.g	1,400
RF min.g	165
PT	20° ± 5°
MD max.	5°
TT min	70°

ISO2768-1 : CLASS OF TOLERANCE		f	m	c	v
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	—
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH

–		–	–	–	–
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
DSND BY U.H LEE	CHKD BY U.H LEE	CHKD BY	APRV BY J.K.HAN	VIEW 3	DATE 2012.01.27
TITLE OUT-LINE DRAWING (SH4140-RL-TAF)			MODEL SH4140-RL-TAF		
Qlight			DWG. NO. SH4140-RL-TAF-OUT		
			SCALE 1/1	SIZE A3	REV 00	SHEET 1/-

A3(420X297)