



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	SW2MS-W
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT,NUT & ETC. - SUS304
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP67
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100M Ω MIN. at 500V DC

Operating Characteristics

OF max.g	1,800
RF min.g	1,400
PT	10°
MD max.	5°
TT min.	50°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-							
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY U.H.LEE	CHKD BY U.H.LEE	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2012.01.27			
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°									
	10~50	±0°30'		±1°	±2°									
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									
TITLE									SW2MS-W OUTLINE DRWAING		MODEL			
											DWG. NO. SW2MS-W-OUT			
											SCALE N/S	SIZE A4	REV 00	SHEET 1/1

Qlight