



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	LZ1710-AL
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT, NUT, ROLLER, LEVER - SUS
CONTACT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d IIC T6 WATER & DUST PROOF - IP67/68
CABLE ENTRY	STANDARD - M20
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

■ Operating Characteristics

OF max.g	1,300
RF min.g	210
PT	15°±5°
MD max.	5°
TT min.	70°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.H.PARK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2018.03.15		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. LZ1710-AL-OUT				
	10~50	±0°30'		±1°	±2°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1	
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								
	TITLE LZ1710-AL OUTLINE DRWAING												MODEL LZ1710-AL