



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO	LZ1710-LRL
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT, NUT, ROLLER, LEVER - SUS
CONTACT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d IIC T6 WATER & DUST PROOF - IP67/68
CABLE ENTRY	STANDARD - M20
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100M Ω MIN. at 500V DC

Operating Characteristics

OF max.g	1,300
RF min.g	210
PT	15° \pm 5°
MD max.	5°
TT min.	70°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-					
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	J.H.PARK	J.H.PARK		J.K.HAN	3	2018.03.15	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			LZ1710-LRL			
	30~120	±0.15	±0.3	±0.8	±1.5	OUTLINE DRWAING			MODEL			
	120~400	±0.2	±0.5	±1.2	±2.5				LZ1710-LRL			
	400~1000	±0.3	±0.8	±2	±4				DWG. NO.			
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'		±3°		LZ1710-LRL-OUT				
	10~50	±0°30'		±1°		±2°		SCALE	SIZE	REV	SHEET	
	50~120	±0°20'		±0°30'		±1°		N/S	A4	00	1/1	
	120~400	±0°10'		±0°13'		±0°30'						