



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	LZ1710-R
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT,NUT,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d IIC T6 WATER & DUST PROOF - IP67/ 68
CABLE ENTRY	STANDARD - M20
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

■ Operating Characteristics	
OF max.g	150
RF min.g	25
PT	15°±5°
MD max.	5°
TT min.	40°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-							
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE		
	3~6			±0.3	±0.5		J.H.PARK	J.H.PARK		J.K.HAN	3	2018.03.15		
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4	TITLE	LZ1710-R OUTLINE DRWAING			MODEL LZ1710-R				
	0~10	±1°	±1°30'	±3°					DWG. NO. LZ1710-R-OUT					
	10~50	±0°30'	±1°	±2°					SCALE	SIZE	REV	SHEET		
	50~120	±0°20'	±0°30'	±1°					N/S	A4	00	1/1		
	120~400	±0°10'	±0°13'	±0°30'										

