



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SNESLR				
MATERIAL			HOUSING-AL				
			LENS-TMPERED GLASS				
			PROTECTION CAGE-ST316L				
			REFLECTOR-PC				
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()				
PER. PER MIN.			120 ~ 140				
USE VOLT.	LED	CURRENT	DC12V		1W	0.485A	
			DC24V			0.411A	
			AC110V			0.111A	
			AC220V			0.055A	
SOUND			Buzzer	Warning Sounds			
VOLUME			MAX. 105dB				
PROTECTION GRADE			WATER & DUST PROOF IP66				
CABLE ENTRY			NPT 1/2"				
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2				
ACTION			LED REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
	400~1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. SNESLR_OUT			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'							